



Model no:
OS-DLNF4MP-36PM



Camera

Image Sensor: 1/3" Progressive Scan CMOS Sensor
Resolution: 4MP
Effective Pixels: 2560(H)*1440(V)
Compression: H.264/H.265/JPEG/AVI/MJPEG
Audio Compression: G711A/U
TV System: PAL/NTSC
Electronic Shutter Time: Auto: 1/3-1/1000000Sec
Minimum Illumination: Color: 0.04 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
S/N Ratio: 60dB
Scanning System: Progressive
Video Output: Network
Reset Button: Optional

Lens

Focal Length & FOV:
2.8 mm, horizontal FOV 100.5°, vertical FOV 55.9°, diagonal FOV 116.9°
3.6 mm, horizontal FOV 78°, vertical FOV 41.8°, diagonal FOV 95.4°
Lens Type: Fixed focal lens, 2.8, and 3.6mm optional
Focus Control: Fixed
Aperture: F2.0
Pixels: 4MP

Night Vision

Infrared LED: 42μ x 2PCS
Infrared Distance: 25M
IR Status: Auto Control
IR Power On: Smart, Manual & Timed mode

Network

Ethernet RJ-45: (10/100Base-T)
Wireless: N/A
Protocol: TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, QoS, 802.1x, PPPoE
ONVIF: Support ONVIF 1.9.12 (Profile S/T)
P2P: YES
POE: Internal, Support IEEE 802.3af
Video Delay: 0.3S (Within the Lan)
Main Stream 1: 2560*1440@25fps
Main Stream 2: 1920*1080@25fps
Main Stream 3: 1280*720@25fps
Sub Stream 1: 720*480@25fps
Sub Stream 2: 640*360@25fps
Sub Stream 3: 352*288@25fps
Tri Stream: N/A
IE Browser: IE8-11, Google Chrome,
Smart Phone: iPhone, Android

AI Functions

Intelligent Analysis: Intrusion Detection, motion detection based on human detection

Camera Features

Day/Night: Color/ B&W (IR-CUT)
Image Config: Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, Anti Flicker, HLC, Distortion
Full Color: N/A
Corridor Pattern: N/A
Defog Mode: N/A
ROI: N/A
BLC: Support
WDR: DWDR
Motion Detection: Support (support enable the detection based on human movement only)
Privacy Masking: 3 Rectangular Zone
Recording Mode: NVR/CMS/Web
Language: Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese

Interface

Audio: Optional 1 Built-in MIC
Alarm: N/A
SD Card Slot: N/A
RS485: N/A

General

Housing: Plastic
Anti-cut Bracket: NO
IR Cut Filter: YES
Operation Temperature: -20°C ~ +60°C RH95% Max
Storage Temperature: -20°C ~ +60°C RH95% Max
Power Source: DC12V±10%, 700mA
Dimension: φ107.34x90.7(H)mm
Weight: 239g

SPECIFICATIONS

+965 9094 1252

+965 9760 3358

info@onesourcekw.com