



Model no: OS-NVR7516-16CH



## Video

**Resolution:** 8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)

**Recording Bandwidth:** Inputs: 112M | Out: 96M

## Performance

### Live/Playback:

**Compression:** Audio: G.711A;G.711U | Video: H.264/H.264+/H.265/H.265+

**Frame Rate:** 4K: 45fps | 4MP: 90fps | 2MP: 180fps

**AI:** yes

**Event:** MD(Sensitivity Level 1~8), Videlo loss, Beep, Email, Push notification to Mobile APP"

**Playback Function:** Fast forward / backward (2x, 4x, 8x, 16x)

Slow Forward (1/2x, 1/4x, 1/8x, 1/16x)

**Playback:** Max 16CH playback

**Fisheye:** Use WEB CMS, device does not support

### UI/Monitoring:

**Local:** UI5.0

**WEB:** IE10/11, Safari V12.1 above, Firefox V.52 above

Google chrome V.57 above, Edge V.79 above

**Mobile Viewer:** Rxcamview

**Push Notification:** yes

## Interface

**P/W Reset:** **Factory Reset:** Press 10 seconds

### Monitors:

**VGA:** 1024\*768, 1280\*720, 1280\*1024, 1440\*900, 1920\*1080

**HDMI:** 1024\*768, 1280\*720, 1280\*1024, 1440\*900, 1920\*1080  
2560\*1440, 3840\*2160/EDID

### Connections:

**POE:** N/A

**Ethernet:** 1 RJ45 100/1000 Base-T

**USB:** USB2.0\*1(front) | USB2.0\*1+(rear)

**Audio Out:** 1

**E-sata:** 1 optional, not supported by default

**HDD:** 2 SATA HDDs, each up to 10TB

**Alarm Input/Out:** 8 in /1 out

## General

**OSD Language:** English / French / Spanish / Portuguese / German  
Italian / Greek / Danish / Finnish / Russia / Hebrew / Turkish  
Bulgarian / Arabic / Korean / Japanese / Thai / Hindi / Romanian  
Dutch / Polish

**Mechanical Design:** Dimension (WxDxH) - 378\*317\*50mm

### Electrical:

**Input Voltage/Current:** DC12V/5A

**Power Consumption (excluding hard disk):** 8W

### Environmental:

**Temperature:** -10°C~+50°C (14°F ~ 122°F)

**Humidity:** Less than 90%RH



# SPECIFICATIONS

+965 9094 1252

+965 9760 3358

info@onesourcekw.com