



Model no: OS-NVR8208-8CH



## Video

### Resolution:

8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)

### Recording Bandwidth:

Inputs 76Mbps, Out 32Mbps

## Performance

### Live/Playback:

Compression: Audio: G.711A,G/711U

Video: H.264/H.264+ / H.265/H.265+

Frame Rate: 4K:30fps | 4MP:60fps | 2MP:120fps

AI: yes

Event: MD(Sensitivity Level 1~8), Video loss, Beep,  
Email Push notification to Mobile APP

Playback Function: Fast forward / backward (2x, 4x, 8x, 16x)

Slow forward (1/2x, 1/4x, 1/8x, 1/16x)

Playback: Max 4CH playback

Fisheye: Use WEB CMS, device does not support

### UI/Monitoring:

Local: UI5.0

WEB: IE10/11, Safari V12.1 above, Firefox V.52 above

Google chrome V.57 above, Edge V.79 above

Mobile Viewer: Rxcamview

Push Notification: yes

## Interface

### P/W Reset:

Factory Reset - Press 10 seconds

### Monitors:

VGA: 1024\*768, 1280\*720, 1280\*1024, 1440\*900, 1920\*1080

HDMI: 1024\*768, 1280\*720, 1280\*1024, 1440\*900, 1920\*1080  
2560\*1440, 3840\*2160 / EDID

### Connections:

POE: 8\*RJ45, 02.3at/af

Ethernet: 1 RJ45 10/100 Base-T

USB: USB2.0\*1(front) | USB2.0\*1(rear)"

Audio out: 1

HDD: 1 SATA HDD, up to 10TB

## General

### OSD Language:

English / French / Spanish / Portuguese / German / Italian / Greek  
Danish / Finnish / Russia / Hebrew / Turkish / Bulgarian / Arabic  
Korean / Japanese / Thai / Hindi / Romanian / Dutch / Polish

### Mechanical Design:

Dimension (WxDxH): 300X227X53mm

### Electrical:

Input Voltage/Current: DC48V/1.5A

Power consumption (excluding hard disk): 6W

### Environmental:

Temperature: -10°C~+50°C (14°F ~ 122°F)

Humidity: Less than 90%RH



# SPECIFICATIONS

+965 9094 1252

+965 9760 3358

info@onesourcekw.com