



Model no:
OS-DLNV4MP-LVDBH



Camera

Image Sensor: 1/3" Progressive Scan CMOS Sensor
Resolution: 4MP
Effective Pixels: 2560(H)*1440(V)
Compression: H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
Audio Compression: G711A/U,AAC
TV System: PAL/NTSC
Electronic Shutter Time: Auto: 1/3-1/1000000Sec
Minimum Illumination:
Color: 0.03 Lux @ (F1.6, AGC ON)
B/W: 0 Lux with IR
S/N Ratio: 60dB
Scanning System: Progressive
Video Output: Network
Reset Button: Optional

Lens

Focus Length: 2.7-13.5mm Motor Zoom, horizontal FOV 98°—28°, vertical FOV 52°—16°, diagonal FOV 118°—32°
Focus Control: Auto
Lens Type: Auto
Aperture: F1.6 - F3.3
Pixels: 4MP

Night Vision

Infrared LED: 42μ x 4PCS
Infrared Distance: 40M
IR Status: Auto Control
IR Power On: Smart, Manual & Timed mode

Network

Ethernet: RJ-45 (10/100Base-T)
Wireless: N/A
Protocol: TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, Qos, 802.1x
ONVIF: Support ONVIF 19.12(Profile S/T/G)
P2P: YES
POE: Internal, Support IEEE 802.3af
Video Delay: 0.3S (Within the Lan)
Main Stream 1: 2688*1512@25fps
Main Stream 2: 2560*1440@30fps
Main Stream 3: 1920*1080@30fps | 1280*720@30fps
Sub Stream 1: 1280*720@30fps
Sub Stream 2: 720*480@30fps
Sub Stream 3: N/A
Tri Stream: N/A
IE Browser: IE8-11, Google Chrome, Firefox, Mac Safari
Smart Phone: iPhone, Android

AI Function

Intelligent Analysis: Intrusion Detection, Motion detection based on human detection

Camera Features

Day/Night: Color/ B&W (IR-CUT)
Image Config: Saturation/Brightness/Contrast/Sharpness, Mirror 3D NR, White Balance, FLK(Flicker Control), Video Tampering HLC, Distortion
Full Color: N/A
Corridor Pattern: Support
Defog Mode: Support
ROI: Support
BLC: Support
WDR: DWDR
Motion Detection: Support (support enable the detection based on human movement only)
Privacy Masking: 3 Rectangular Zone
Recording Mode: NVR/CMS/Web
Language: Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese

Interface

Audio: Optional Audio IN/OUT
Alarm: N/A
SD Card Slot: Optional Internal, Support Max 512GB
RS485: N/A

General

Housing: Metal, IP67
Anti-cut Bracket: NO
IR Cut Filter: YES
Operation Temperature: -20°C ~ +60°C RH95% Max
Storage Temperature: -20°C ~ +60°C RH95% Max
Power Source: DC12V±10%, 950mA
Dimension: φ 140 x 128(H)mm
Weight: 1200g



SPECIFICATIONS

+965 9094 1252 ☎
+965 9760 3358
info@onesourcekw.com ✉